



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359  
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

## TECHNICAL INFORMATION

### ACRYLIC EMULSION

<b>PRODUCT DESCRIPTION:</b>	<b>ACRYLIC EMULSION</b> is made up of water based acrylic emulsion.
<b>FIELD OF USE:</b>	It is used for the impregnation of façade plaster (façades, inner walls), concrete... Pre-treatment with emulsion and half-emulsion paints is recommended, while it gives solid adhesion for paint.
<b>SURFACE PREPARATION:</b>	We must remove the dust and breakable parts.
<b>PAINT PREPARATION:</b>	We mix <b>ACRYLIC EMULSION</b> for the application.
<b>APPLICATION:</b>	It can be manipulated by brush or roller.
<b>THEORETICAL COVERAGE:</b>	Theoretical application rate is 80-100ml/m <sup>2</sup> .
<b>DRYING TIME:</b>	The coating is dry after 4 hours(20°C). Only one coat is necessary.
<b>PHYSICAL PROPERTIES:</b>	
<b>COLOR SHADES:</b>	Whitely, after drying out it is colorless.
<b>ODOUR:</b>	Typical
<b>APPEARANCE:</b>	Liquid
<b>DENSITY:</b>	1,05 g/ml (20°C)
<b>THINNING AND CLEANING:</b>	Water
<b>PACKAGING:</b>	1l, 5l, 10l, 20l.
<b>WAREHOUSING:</b>	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
<b>NOTE:</b>	Transport is possible only at temperatures higher than 5°C; otherwise the vehicle must be heated. The same applies for storing.

*barve ki ščitijo vaš dom*