



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

ACRYLFAS

PRODUCT DESCRIPTION:	ACRYLFAS is steam-permeable façade paint. It is made up of acrylic binders, UV-rays resistant pigments and organic solvents.
FIELD OF USE:	Façade and concrete
SURFACE PREPARATION:	The surface must be clean, dry and well prepared surfaces of the façade.
PAINT PREPARATION:	first coat diluted with 10% and second coat with 5% of ALKIDKOLOR DILUENT
APPLICATION:	For application of the impregnation and paint we use rollers, brushes or airless equipment. The paint should be at least 15°C during the application. The air temperature may not drop below 0°C.
THEORETICAL COVERAGE:	ACRYLFAS IMPREGNANT: 0,15 – 0,3l/m ² ACRYLFAS: 20 – 25 dkg/m ²
LAYER APPLICATION TIME:	Single application allowed after 24 hours.
PHYSICAL PROPERTIES:	
COLOR SHADES:	white or colorful in color charts
APPEARANCE:	Dense liquid
DENSITY:	cca. 1 g/ml (20°C)
THINNING AND CLEANING:	ALKIDKOLOR DILUENT
PACKAGING:	1kg and 25kg.
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	The paint should be at least 15°C during the application. The air temperature may not drop below 0°C.

barve ki ščitijo vaš dom