



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359  
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

## TECHNICAL INFORMATION

### BIOBEL

<b>PRODUCT DESCRIPTION:</b>	<b>BIOBEL</b> acrylic white paint for inner walls and ceilings is environment friendly, based on acrylic binders, pigments and qualitative fillings. It is used for all wall types from the cellar to the attic. The walls should be horizontal and vertical isolated, the rooms aired.
<b>FIELD OF USE:</b>	<b>BIOBEL</b> is washable paint for inside the building and suitable for plaster linings.
<b>SURFACE PREPARATION:</b>	Before application the surface should be cleaned, levelled with mineral or dispersion putty and slightly whetted. The solid wall can be impregnated with <b>BIOBEL</b> and water (1:1).
<b>PAINT PREPARATION:</b>	<b>BIOBEL</b> should be well mixed and diluted with 15% of water. After application we clean the tools with water.
<b>APPLICATION:</b>	The paint should be applied on the wall with roller or brush. Two coats are necessary.
<b>THEORETICAL COVERAGE:</b>	cca 250g/m <sup>2</sup> for one coating.
<b>DUST DRY:</b>	90 minutes
<b>DRY ON CONTACT:</b>	180 minutes
<b>NEXT LAYER:</b>	6 hours
<b>PHYSICAL PROPERTIES:</b>	
<b>COLOR SHADES:</b>	white, mixed with dispersion pastes or paints.
<b>DENSITY:</b>	1,55 g/ml (at 20°C)
<b>SOLID VALUE:</b>	70±2%
<b>VISCOSITY:</b>	Thick pasty fluid
<b>THINNING AND CLEANING:</b>	Water
<b>PACKAGING:</b>	3kg, 8kg, 25kg
<b>WAREHOUSING:</b>	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
<b>NOTE:</b>	Must not freeze.

*barve ki ščitijo vaš dom*