



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

DISTEMPERA

PRODUCT DESCRIPTION:	DISTEMPERA paint for inner walls is environment friendly, based on synthetic binders, mineral fillings and special additives. It can be used for walls and ceilings from the cellar to the attic, which are not damp. The walls should be horizontal and vertical isolated, the rooms aired.
FIELD OF USE:	It can be used for walls and ceilings from the cellar to the attic, which are not damp.
SURFACE PREPARATION:	Before application the surface should be cleaned, levelled with mineral or dispersion putty and slightly whetted. The solid wall should be coated with acrylic emulsion.
PAINT PREPARATION:	DISTEMPERA should be well mixed and diluted with 0,1l water on 1l paint (10%). After application we clean the tools with water.
APPLICATION:	The paint should be applied on the wall with roller or brush. Two coats are necessary.
THEORETICAL COVERAGE:	Theoretical use is 90-100g/m ² enough for one coating.
DUST DRY:	90 minutes
DRY ON CONTACT:	180 minutes
NEXT LAYER:	6 hours
PHYSICAL PROPERTIES:	
COLOR SHADES:	white, pastel shades in different color charts
ODOUR:	Typical
DENSITY:	1,56 g/ml (20°C)
SOLID VALUE:	65±2
VISCOSITY:	Viscose liquid
THINNING AND CLEANING:	Water
PACKAGING:	3l, 5l, 15l
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	Temperature must not drop below 5°C.

barve ki ščitijo vaš dom