



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359  
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

## TECHNICAL INFORMATION

### EKO FAS

- PRODUCT DESCRIPTION:** **EKO FAS** is façade paint, environment friendly and based on natural binders, mineral fillings, inorganic pigments and special natural additives for color durability.
- FIELD OF USE:** Different types of walls, which are already prepared with mineral plaster, can be coated. That applies for damp walls such as: humid cellars, stables, churches... The paint is **STEAM-PERMEABLE**.
- SURFACE PREPARATION:** Before application the wall should be cleaned, levelled with mineral or dispersion putty and slightly whetted.
- PAINT PREPARATION:** Before the first coating it should be well mixed and diluted with 40-50% of water. For the second coating it is less diluted. T After application we clean the tools with water.
- APPLICATION:** The paint should be applied onto walls with roller or brush. Two coats are necessary.
- THEORETICAL COVERAGE:** Theoretical application rate is 200g/m<sup>2</sup> enough for one coating.
- DUST DRY:** 90 minutes
- DRY ON CONTACT:** 180 minutes
- NEXT LAYER:** 8 hours
- PHYSICAL PROPERTIES:**
- COLOR SHADES:** white, pastel shades in different color charts
- ODOUR:** Typical
- DENSITY:** 1,50 g/ml (20°C)
- SOLID VALUE:** 65 ± 2%
- THINNING AND CLEANING:** Water
- PACKAGING:** 1kg, 8kg, 25kg
- WAREHOUSING:** At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
- NOTE:** Temperature must not drop below 5°C. The paint is **STEAM-PERMEABLE**.

*barve ki ščitijo vaš dom*