



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

EKOKRIL

PRODUCT DESCRIPTION:	EKOKRIL – ACRYLIC WATER BASED PARQUET VARNISH is water based parquet varnish made up of acrylic binders.
FIELD OF USE:	EKOKRIL is used for parquet, wooden floor, wall linings and furniture.
SURFACE PREPARATION:	Before application on the wooden surface that contains tannin (oak, chestnut), it should be protected with special water based impregnant or NITRO FOUNDATION VARNISH .
PAINT PREPARATION:	It is diluted with water (first coating 15-20% and second coating 10% of water).
APPLICATION:	The varnish can be applied on smoothly whetted surfaces with brush, roller, by spattering or casting over.
THEORETICAL COVERAGE:	Theoretical application rate is 70-100g/m ² - enough for one coating.
NEXT LAYER:	Single coats can be whetted with fine sandpaper after 2-3 hours at 20°C.
PHYSICAL PROPERTIES:	
COLOR SHADES:	gloss, silky matt, semi-matt, and matt
HARDNESS:	171s (gloss), 166s (silky matt) - KOENIG
GLOSS:	94-96% (gloss); 50-53% (silky matt)
DENSITY:	1,03 g/ml (20°C)
SOLID VALUE:	33 ± 2 %
VISCOSITY:	40 s (F4 mm 20°C) - gloss
THINNING AND CLEANING:	Water
PACKAGING:	1l, 5l, 10l, 20l
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	

barve ki ščitijo vaš dom