



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

GRUNDALKYD COATING

PRODUCT DESCRIPTION:	GRUNDALKYD COATING is an anticorrosive foundation coating, made up of synthetic binders, iron-oxide and zinc-phosphate anticorrosive pigments and solvents, and other additives for good adhesion and has the ability to stick to metal and wood. It binds the coats together.
FIELD OF USE:	It is used as a foundation for metal and wooden constructions, for doors, fences, windows...
SURFACE PREPARATION:	The surface should be dry, without greasy and dusty spots. Rust should be scraped off.
PAINT PREPARATION:	It must be well mixed and diluted with ALKIDKOLOR DILUENT . Dilution depends on application method.
APPLICATION:	The paint is manipulated by brush, roller, by spattering or dipping.
THEORETICAL COVERAGE:	Theoretical application rate is 125g/m ² for a dry film thickness 60µm.
DRY ON CONTACT:	2 hours
NEXT LAYER:	after 24 hours
PHYSICAL PROPERTIES:	
COLOR SHADES:	oxide red and grey for metal, white for wood
ODOUR:	Typical after alkyd
APPEARANCE:	Viscose liquid
DENSITY:	1,48 g/ml (20°C)
SOLID VALUE:	72 ± 2%
VISCOSITY:	140s (F6 20°C)
HARDNESS:	58 s KOENIG
GRASP:	0
GLOSS - LANG 60	8,00%
ELASTICITY ERICH	8 mm
THINNING AND CLEANING:	ALKIDKOLOR DILUENT
PACKAGING:	0,3kg, 1kg, 6kg, 30kg or 0,75l
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	

barve ki ščitijo vaš dom