



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

LESOTON AQUA

PRODUCT DESCRIPTION:	LESOTON AQUA stains are acrylic water based paints for protection of wooden surfaces outside and inside the building.
FIELD OF USE:	LESOTON AQUA is used for wood lining, for wooden balcony fences, windows, balcony and front doors.
SURFACE PREPARATION:	The air-dried wood should be cleaned.
PAINT PREPARATION:	The paint must be well mixed.
APPLICATION:	LESOTON AQUA is applied with brush or roller, and by dipping or spattering. One coat of LESOTON AQUA IMPREGNATION is applied first, then one thin-coat of LESOTON AQUA stain and at the end 2 coats of LESOTON AQUA lacquer.
THEORETICAL COVERAGE:	Theoretical application rate for LESOTON AQUA IMPREGNATION is 100g/m ² and for LESOTON AQUA stain 120g/m ² .
DUST DRY:	2 hours
DRY ON CONTACT:	4 hours
NEXT LAYER:	after 6 hours (impregnation after 4 hours).
PHYSICAL PROPERTIES:	
COLOR SHADES:	Impregnation: colorless, yellow, brown, green and other samples. Stain: pine, oak, maple, mahogany, teak, nut and other samples.
ODOUR:	Typical
DENSITY:	cca 1,00 g/ml – depends on the shade
pH	cca 8
THINNING AND CLEANING:	Water
PACKAGING:	1l, 5l, 10l, 20l, 30l, 120l, 150l.
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	Temperature must not drop under 5°C.

barve ki ščitijo vaš dom