

Application:

EFEKT LAZURA coloured lack lasur is esthetical, decorative and protective coating for exterior and interior surfaces of wood. It is used for protection of façade linings, windows, doors and other weather exposed joinery.

Characteristics:

- provides excellent weather resistance
- contains no biocides
- easy to apply
- suitable for all types of wood both indoors and outdoors



EFEKT LAZURA
Coloured lack lasur



INSTRUCTIONS FOR USE

| | |
|------------------------------|--|
| PAINT PREPARATION: | It should be well mixed. |
| SURFACE PREPARATION: | The air-dried wood should be cleaned. |
| APPLICATION: | It can be manipulated by brush, roller, air pistol or airless spraying. It is used as last layer of wood protection. |
| THEORETICAL COVERAGE: | For one layer we use cca. 0,1L of EFEKT LAZURA on m ² |
| DRYING TIME: | Dust dry after 2 hours, on contact after 6 hours. |
| NEXT LAYER: | Single coatings should be applied after 24 hours, except by industrial procedures. |

TECHNICAL DATA

| | |
|------------------------------------|--|
| COLOR SHADES: | colorless, white, pine, teak, oak, walnut, green, blue, mahogany, palisander, black-ebony and others on customer wish. |
| APPEARANCE | colored liquid |
| DENSITY: | 0,9 g/ml (20°C) |
| EU VOC category and limits: | IIA(e): 400 g/l (2010); the product contains; max. 400 g/l |
| THINNING AND CLEANING: | ALKIDKOLOR DILUENT. Before using it is not allowed to dilute, except in industrial procedures. |
| PACKAGING: | 0,75l, 1l, 2,5l, 4l, 5l, 10l, 25l, 200l. |
| SHELF LIFE | At least 36 months in originally sealed and undamaged packaging, in a dry and well ventilated place. |

SYSTEM

| SURFACE | PREPARATION | PRIMER | TOP COAT |
|---------|---|---------------------------|-----------------|
| WOOD | The surface must be dry, without greasy and dust marks. | LESOLIT FIX LESOTON 2X | EFEKT LAZURA 1X |

REMARKS:

- After work EFEKT LAZURA should be stored in full and tightly closed packaging. Paint rests should be filled together and airtight closed. It can polymerize.

