

Application:

LESOTON protection stain for wood is esthetical, decorative and protective coating for exterior and interior surfaces of wood. It is used for protection of façade linings, windows, doors and other weather exposed joinery.

Characteristics:

- provides excellent weather resistance
- contains no biocides
- easy to apply
- suitable for all types of wood both indoors and outdoors



LESOTON
Coloured wood
protection



INSTRUCTIONS FOR USE

PAINT PREPARATION: It should be well mixed.

SURFACE PREPARATION: The air-dried wood should be cleaned.

APPLICATION: It can be manipulated by brush, roller, air pistol or airless spraying. There are 3 coats necessary for an effective protection (for interior protection only 2 coats). Single coatings should be applied after 24 hours, except by industrial procedures. For the last layer LESOTON EFEKT LAZURA in selected shade should be used.

THEORETICAL COVERAGE: For one layer we use cca. 0,1L of LESOTON on m²

DRYING TIME: Dust dry after 2 hours, on contact after 6 hours.

NEXT LAYER: Single coatings should be applied after 24 hours, except by industrial procedures.

TECHNICAL DATA

COLOR SHADES: colorless, white, pine, teak, oak, walnut, green, blue, mahogany, palisander, black-ebony and others on customer wish.

APPEARANCE colored liquid

DENSITY: 0,9 g/ml (20°C)

EU VOC category and limits: IIA(f): 700 g/l (2010); the product contains; max. 610 g/l

THINNING AND CLEANING: **ALKIDKOLOR DILUENT.** Before using it is not allowed to dilute, except in industrial procedures.

PACKAGING: 0,75l, 1l, 2,5l, 4l, 5l, 10l, 25l, 200l.

SHELF LIFE At least 36 months in originally sealed and undamaged packaging, in a dry and well ventilated place.

SYSTEM

SURFACE	PREPARATION	PRIMER	TOP COAT
WOOD	The surface must be dry, without greasy and dust marks.	LESOLIT FIX	LESOTON 2X EFEKT LAZURA 1X

REMARKS:

- After work LESOTON should be stored in full and tightly closed packaging. Paint rests should be filled together and airtight closed. It can polymerize.

