



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

LINSEED OIL

PRODUCT DESCRIPTION:	LINSEED OIL - the air-drying oil obtained from the seeds. Therefore it dries very slowly. Linseed oil is not weather-resistant.
FIELD OF USE:	It is an impregnation agent for different materials (wood, stone).
SURFACE PREPARATION:	Grind off the edges and remove the dust
PAINT PREPARATION:	The paint must be mixed, before usage. Oil can be heated up (30-40°C), in order to achieve better absorption
APPLICATION:	We can apply LINSEED OIL with brush, roller or by soaking
THEORETICAL COVARAGE:	It depends on the type and dryness of the wood: 60–100g/m ²
NEXT LAYER:	It depends on the type of wood and film thickness: cca. 24h
PHYSICAL PROPERTIES:	
COLOR SHADES:	Yellowish-brown
ODOUR:	Typical
APPEARANCE:	Oil (viscose liquid)
DENSITY:	0,93 g/ml (20°C)
THINNING AND CLEANING:	/
PACKAGING:	0,5l, 1l, 5l, 25l and 200l
WAREHOUSING:	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
NOTE:	

barve ki ščitijo vaš dom