



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359  
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

## TECHNICAL INFORMATION

### LINSEED VARNISH

<b>PRODUCT DESCRIPTION:</b>	<b>LINSEED VARNISH</b> is made up of linseed oil. It can be used as an additive for paints, lacquers and stains and enlarges the drying and moisture resistance. Siccative agents are added into the varnish.
<b>FIELD OF USE:</b>	It is used for impregnation (wood fancy goods, other wood goods and stone).
<b>SURFACE PREPARATION:</b>	Grind off the edges and remove the dust
<b>PAINT PREPARATION:</b>	The varnish must be mixed, before usage. Oil can be heated up (30-40°C), in order to achieve better absorption
<b>APPLICATION:</b>	We can apply <b>LINSEED VARNISH</b> with brush, roller or by soaking
<b>THEORETICAL COVERAGE:</b>	It depends on the type and dryness of the wood: 60–100g/m <sup>2</sup>
<b>NEXT LAYER:</b>	It depends on the type of wood and film thickness: cca. 24h
<b>PHYSICAL PROPERTIES:</b>	
<b>COLOR SHADES:</b>	Yellowish-brown
<b>ODOUR:</b>	typical
<b>APPEARANCE:</b>	Oil (viscose liquid)
<b>DENSITY:</b>	0,93 g/ml (20°C)
<b>THINNING AND CLEANING:</b>	/
<b>PACKAGING:</b>	0,5l, 1l, 5l, 10l, 25l, 200l
<b>WAREHOUSING:</b>	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
<b>NOTE:</b>	

*barve ki ščitijo vaš dom*