



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359  
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

## TECHNICAL INFORMATION

### SIMPLE LAK

<b>PRODUCT DESCRIPTION:</b>	<b>SIMPLE LAK</b> is a one-component polyurethane parquet varnish based on synthetic binders.
<b>FIELD OF USE:</b>	SIMPLE LAK is suitable for lacquering of parquets, floor and wall wood linings. It is resistant to wearing out. Its hardness (206 second/Koenig) enables to use SIMPLE LAK for very burdened surfaces (gymnasiums, offices...).
<b>SURFACE PREPARATION:</b>	The floor must be smoothly whetted and dust free.
<b>PAINT PREPARATION:</b>	The first coating is diluted with 15-20% of <b>SIMPLE DILUENT</b> , further coatings with 10% of the diluent.
<b>APPLICATION:</b>	It should be applied on smoothly whetted surfaces with brush, roller or by spattering or casting over. The relative humidity in the room should be 75%.
<b>THEORETICAL COVERAGE:</b>	Theoretical application rate is 70-100g/m <sup>2</sup> - enough for one coating.
<b>NEXT LAYER:</b>	Single coats can be whetted with fine sandpaper after 6 hours at 75% relative air humidity and 20°C.
<b>PHYSICAL PROPERTIES:</b>	
<b>COLOR SHADES:</b>	gloss, silky matt, semi-matt, and matt
<b>DENSITY:</b>	1,00 g/ml (20°C)
<b>SOLID VALUE:</b>	39 ± 2 % (mixture)
<b>VISCOSITY:</b>	24 s (F4 mm 20°C)
<b>HARDENESS:</b>	206s (Koenig)
<b>GLOSS:</b>	94,4% (gloss)
<b>THINNING AND CLEANING:</b>	<b>SIMPLE DILUENT</b>
<b>PACKAGING:</b>	1l, 5l, 10l
<b>WAREHOUSING:</b>	At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
<b>NOTE:</b>	

*barve ki ščitijo vaš dom*