



Chemcolor Sevnica d.o.o., Dolnje Brezovo 35, 8290 Sevnica, Identifikacijska številka za DDV: SI24218359
Tel.: +386 (0)7 81 63 550 / 81 60 100 Fax.: +386 (0)7 81 63 564 / 81 60 101 www.chemcolor.si

TECHNICAL INFORMATION

STREET PAINT

- PRODUCT DESCRIPTION:** **STREET PAINT** designed in white and yellow. It is used for street marking, for parking lots...It is applied by spattering. It has a good adhesive strength on asphalt, stone and concrete. The painted surface has a good light reflection. The applied paint dries quickly. After 25 minutes it is possible to drive without damaging the street. It excels in flexibility, in resistance from weather influence, water, and light, ageing and wearing out. Traffic safety is possible for at least 12 months.
- FIELD OF USE:** The paint can be used very successfully for marking playgrounds, for painting façades and sanitation of walls on very exposed places.
- SURFACE PREPARATION:** Before painting, the surface must be cleaned from dust, oil, organic and inorganic dirtiness.
- PAINT PREPARATION:** It can be diluted with **STREET PAINT DILUENT**.
- APPLICATION:** It can be manipulated by spattering, with brush or roller. Less than 250µm wet film thickness can not be applied. On much burdened surfaces it is recommended to apply 400-600µm of the wet film thickness. On the painted surface we can add reflex pearls (pearl thickness 125-500µm). The pearl application must follow right after the painting, after 5 seconds (not later), because of the adhesive strength.
- THEORETICAL COVERAGE:** cca 370g/m² for 250µm, cca 580g/m² for 400µm...
- DRYING TIME:** Drying time of the wet film thickness (250µm) is 15-25 minutes at 20°C.
- PHYSICAL PROPERTIES:**
- COLOR SHADES:** white and yellow, any shade when ordering over 600kg.
- DENSITY:** 1,45 ± 0,5% g/ml
- SOLID VALUE:** 70 ± 2%
- VISCOSITY:** 4000-5000 cP (po DIN 53211/20°C with BROOKFIELD VISC.)
- THINNING AND CLEANING:** **STREET PAINT DILUENT**
- PACKAGING:** 1,3kg, 6kg, 30kg.
- WAREHOUSING:** At least 12 months in originally sealed and undamaged packaging, in a dry and well ventilated place.
- NOTE:**

barve ki ščitijo vaš dom